

OWS Multilight LXI SAE 10W-40

HC-Synthetic High Performance Light-Running Engine Oil

Product Description:

OWS Multilight LXI SAE 10W-40 is a high-performance light-running HC-synthetic engine oil designed for use in modern engines with tight tolerances. It delivers excellent performance and fuel economy properties.

OWS Multilight LXI SAE 10W-40 is manufactured using the highest quality HC-Synthetic base oils and state of the art Überclean® additive technology. This ensures a finished product with an unmatched performance level.

OWS Multilight LXI SAE 10W-40 is an ideal choice for most gasoline and diesel engines, including turbo-charged and non-turbo-charged engines, and can be used year round in most climates.

OWS Multilight LXI SAE 10W-40 fulfils or exceeds the following specifications:

ACEAA3/B3/B4

API SN/CF

MB 229.1

Ford ESE-M2C 153-E

VW 501 01 / 505 00 (OEM Approval)

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052	kg/L	0.868
Kinematic Viscosity @40°C	ASTM D445	cSt	91.8
Kinematic Viscosity @100°C	ASTM D445	cSt	14.2
Viscosity Index	ASTM D2270		137
Flash Point, COC	ASTM D92-05A	°C	> 200
Pour Point	ASTM D97	°C	< -30

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification.

All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.