

OWS Synthomax SAE 0W-30

Fully Synthetic Universal Engine Oil for Diesel and Gasoline Engines

Product Description:

OWS Synthomax SAE 0W-30 is a Top-Class multi-grade fully synthetic ester based formulation that protects against friction, heat and corrosion, keeping engines healthy and efficient. OWS Übercleal additives reduce carbon and sludge build-up even under severe driving conditions.

OWS Synthomax SAE 0W-30 is excellently suited for use in passenger car gasoline and diesel engines, both turbo-charged and non-turbo-charged.

OWS Synthomax SAE 0W-30 fulfils or exceeds the following specifications:

ACEAA3 / B4

API SN/CF

VW50500/50500

BMW Longlife-01 MB 229.3

PSA B71 2296

| Test | Method | Unit | Result |
|----------------------------|------------------|------|--------|
| Density @ 15°C | ASTM D4052-09 | kg/L | 0.845 |
| Kinematic Viscosity @40°C | ASTM D445-10 | cSt | 72.0 |
| Kinematic Viscosity @100°C | ASTM D445-10 | cSt | 12.5 |
| Viscosity Index | ASTM D2270-04 | | 174 |
| Flash Point, COC | ASTM D92-05A(10) | °C | > 200 |
| Pour Point | ASTM D97-09 | °C | < -50 |
| | | | |

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification.

All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.