

OWS Super Turbo SAE 15W-50

Super Protection Performance HC Fully Synthetic Engine Oil

Product Description:

OWS Super Turbo SAE 15W-50 is a high performance multigrade engine oil for modern car engines in any operating conditions and is preferred in Southern Europe countries. The great performance reserve of OWS Super Turbo SAE 15W-50 is achieved by a specific combination of base oils using synthetic technology and modern innovative additives. The use of these additives effectively prevents sludge development, wear and corrosion. The low evaporation loss base oils and good compatibility with seals clearly reduce oil consumption. Application OWS Super Turbo SAE 15W-50 is recommended for passenger car gasoline and diesel engines.

Specifications :

- SAE Grade 15W-50
- ACEA A3/B4
- API SN/CF

Typical Properties:

SAE Grade: **15W50**

Test	Method	Unit	Result
SAE Grade	DIN 51 511		15W-50
Density @15°C	DIN 51 757	g/cm ³	0.874
Viscosity at -20°C	ASTM D 5293	mPa s	5,830
Viscosity at 40°C	DIN EN ISO 3104	mm ² /s	139
Viscosity at 100°C	DIN EN ISO 3104	mm ² /s	18.4
Viscosity Index	DIN ISO 2909		148
Flash point COC	DIN ISO 2592	°C	238
Pour point	DIN ISO 3016	°C	-39
Sulphated ash	DIN 51 575	g/100 g	0.96

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.