

OWS Truck Ultra SAE 10W-40

Premium high-performance engine oil

Product Description:

OWS Truck Ultra SAE 10W-40 ensures excellent long-term performance for heavy duty engine applications that operate in all climates under high-load and high-stress conditions.

OWS Truck Ultra SAE 10W-40 Engine Oil contains field proven additive technology delivering maximum control on engine wear, outstanding engine cleanliness, and high TBN retention for outstanding lubricant life.

Exceeds all requirements of current emission control systems & API service category CK-4 for high-performance diesel engines that are operated with Ultra Low Sulfur Diesel (ULSD).

Typical Properties:

Characteristic	Units	ASTM Method	Test Result
Appearance	-	Visual	B & C
Color	-	D 1500	3.5
Density @ 15 °C	kg/l	D 4052	0.8710
Density @ 20 °C	kg/l	D 4052	0.8678
Flash Point COC	°C	D 92	218
Pour Point	°C	D 97	-30
CCS	cP	D 5293	6089
HTHS	cP	D 5481	3.52
Density @ 30 °C	kg/l	D 4052	0.8615
Kinematic Viscosity @ 40°C	cSt	D 445	108.4
Kinematic Viscosity @ 100°C	cSt	D 445	15.23
Viscosity Index	-	D 2270	147
Total Base Number	mgKOH/g	D 2896	9.8

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.