

OWS Multilite LA SAE 15W-40

High Performance Fuel Economy Engine Oil for Low Ash SHPD Class Commercial Vehicles

Product Description:

OWS Multilite LA SAE 15W-40 is a high performance multigrade fuel economy SHPD (Super High Performance Diesel) engine oil developed for the latest generation of utility and commercial vehicles with after gas treatment systems. OWS Überclean® additive technology protects your engine enhances performance, minimizing wear and maintenance costs.

Specifications :

ACEA E9; API SN / CJ-4; CAR ECF-3 / -2 / -1-a; Cummins CES 20081; DDC 93K218; Deutz DQC III-10 LA; Mack E0-0 Premium Plus; MAN M3575; MB 228.31; MTU Typ 2.1; Renault RLD-3; Volvo VDS-4

Typical Properties:

SAE Grade: **15W40**

Test	Method	Unit	Result
Density @ 15°C	ASTM D-7042	kg / L	0.8872
Kinematic Viscosity @40°C	ASTM D-7042	cSt	103
Kinematic Viscosity @100°C	ASTM D-7042	cSt	14.0
Viscosity Index	ASTM D-7042		138
Flash Point, COC	ASTM D-92	°C	221
Pour Point	ASTM D-97	°C	-30
Base Number	DIN 51639-1	mg KOH/g	11.96

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification.
All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.